

La coppia trasmissibile indicata si riferisce al valore massimo trasmesso in condizioni teoriche.

La coppia reale dipende da fattori esterni quali:

- Allineamento degli alberi;
- Picchi;
- Vibrazioni.

Si consiglia perciò di considerare un fattore peggiorativo nel dimensionamento delle trasmissioni a seconda delle reali condizioni di lavoro.

Si raccomanda inoltre l'ingrassaggio degli scanalati (alberi e giunti) per preservare più a lungo l'integrità dei denti.


The allowed torque is referred to the maximum value transmitted under theoretical conditions.

The real torque rating depends on external factors such as:

- *shaft alignments;*
- *peaks;*
- *vibrations.*

We recommend therefore to take into consideration a negative factor while calculating the transmissions based onto real working conditions.

Furthermore, we recommend to grease the splined shafts (couplings and joints) to ensure longer lifetime to the toothing.

11400300014  6x21x25 (ISO 14) Coppia teorica trasmissibile Theoretical transmitted torque 400 Nm	Manicotto / Hub UNI - UNI 11400000106  Lunghezza Length 30mm 11400010604 	
11400400059  19x22 Z=13 (DIN 5482) 6x21x25 (ISO 14) Coppia teorica trasmissibile Theoretical transmitted torque 250 Nm	Manicotto / Hub UNI / DIN - UNI / DIN 11400000115  Lunghezza Length 30mm 11400011505 	